



SAFETY DATA SHEET

Regular BCM Dry Chemical (Fire Extinguishing Agent - Pressurized and Non-pressurized)

1. IDENTIFICATION

Product Name	Regular BCM Dry Chemical (Fire Extinguishing Agent Pressurized and Non-pressurized)
Other Names	Regular, Stearated B:C, Sodium Bicarbonate, BCM
Recommended use of the chemical and restrictions on use	
Identified uses	Fire Extinguishing Agent
Restrictions on use	Consult applicable fire protection codes
Company Identification	Badger Fire Protection 944 Glenwood Station Lane, Suite 303 Charlottesville, VA 22901 USA
Customer Information Number	(434)-964-3200
Emergency Telephone Number	
CHEMTREC Number	(800) 424-9300 (703) 527-3887 (International)
Issue Date	November 23, 2016
Supersedes Date	October 1, 2015

Safety Data Sheet prepared in accordance with OSHA's Hazard Communication Standard (29 CFR 1910.1200) and the Globally Harmonized System of Classification and Labelling of Chemicals (GHS)

2. HAZARD IDENTIFICATION

This SDS covers the product listed above as sold in pressurized and non-pressurized containers. GHS classifications for both forms are listed below.

GHS Classification – Pressurized

Hazard Classification

Gas under pressure – Compressed gas

Label Elements

Hazard Symbols



Signal Word: Warning

Hazard Statements

Contents under pressure; may explode if heated.



SAFETY DATA SHEET

Regular BCM Dry Chemical (Fire Extinguishing Agent - Pressurized and Non-pressurized)

2. HAZARD IDENTIFICATION

Precautionary Statements

Prevention

None

Response

None

Storage

Protect from sunlight.

Store in well-ventilated place.

Disposal

None

GHS Classification: Non - pressurized

Hazard Classification

This product is classified as not hazardous in accordance with the Globally Harmonized System of Classification and Labelling (GHS).

Label Elements

Hazard Symbols

None

Signal Word: None

Hazard Statements

None

Precautionary Statements

Prevention

None

Response

None

Storage

None

Disposal

None

Other Hazards

Mica may contain small quantities of quartz (crystalline silica) as an impurity. Prolonged exposure to respirable crystalline silica dust at concentrations exceeding the occupational exposure limits may increase the risk of developing a disabling lung disease known as silicosis. IARC found limited evidence for pulmonary carcinogenicity of crystalline silica in humans.

Specific Concentration Limits

The values listed below represent the percentages of ingredients of unknown toxicity.

Acute oral toxicity < 10%

Acute dermal toxicity < 10%

Acute inhalation toxicity < 10%

Acute aquatic toxicity < 10%



SAFETY DATA SHEET

Regular BCM Dry Chemical (Fire Extinguishing Agent - Pressurized and Non-pressurized)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: Regular, Stearated B:C, Sodium Bicarbonate, BCM
This product is a mixture.

Component	CAS Number	Concentration
Sodium Bicarbonate	144-55-8	85 - 95%
Mica	12001-26-2	1 - 5%
Clay	8031-18-3	1 - 5%
Calcium Stearate	66071-81-6	1 - 5%

Note: Pressurized product uses nitrogen or compressed air as the expellant.

4. FIRST- AID MEASURES

Description of necessary first-aid measures

Eyes

Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

Skin

Wash skin thoroughly with soap and water. Obtain medical attention if irritation persists.

Ingestion

Dilute by drinking large quantities of water and obtain medical attention.

Inhalation

Move victim to fresh air. Obtain medical attention immediately for any breathing difficulty.

Most important symptoms/effects, acute and delayed

Aside from the information found under Description of necessary first aid measures (above) and Indication of immediate medical attention and special treatment needed, no additional symptoms and effects are anticipated.

Indication of immediate medical attention and special treatment needed

Notes to Physicians

Treat symptomatically.

5. FIRE - FIGHTING MEASURES

Suitable Extinguishing Media

This preparation is used as an extinguishing agent and therefore is not a problem when trying to control a blaze. Use extinguishing agent appropriate to other materials involved. Keep pressurized containers and surroundings cool with water spray as they may rupture or burst in the heat of a fire.

Specific hazards arising from the chemical

Pressurized containers may explode in heat of fire.

Special Protective Actions for Fire-Fighters

Wear full protective clothing and self-contained breathing apparatus as appropriate for specific fire conditions.



SAFETY DATA SHEET

Regular BCM Dry Chemical (Fire Extinguishing Agent - Pressurized and Non-pressurized)

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear appropriate protective clothing. Prevent skin and eye contact. Remove leaking container to a safe place. Ventilate the area.

Environmental Precautions

Prevent large quantities of the material from entering drains or watercourses.

Methods and materials for containment and cleaning up

Sweep up or vacuum and transfer into suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Wear appropriate protective clothing. Prevent skin and eye contact.

Conditions for safe storage

Pressurized containers should be properly stored and secured to prevent falling or being knocked over. Do not drag, slide or roll pressurized containers. Do not drop pressurized containers or permit them to strike against each other. Never apply flame or localized heat directly to any part of the pressurized or plastic container. Store pressurized and plastic containers away from high heat sources. Storage area should be:
- cool - dry - well ventilated - under cover - out of direct sunlight

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Mica

ACGIH TLV: 3 mg/m³ TWA, measured as respirable fraction of the aerosol.

OSHA PEL: 20 mppcf, <1% crystalline silica

Nuisance Dust Limit

OSHA PEL: 50 mppcf or 15 mg/m³ TWA, total dust

15 mppcf or 5 mg/m³ TWA, respirable fraction

Appropriate engineering controls

Use with adequate ventilation. If this product is used in a pressurized system, there should be local procedures for the selection, training, inspection and maintenance of this equipment. When used in large volumes, use local exhaust ventilation.

Individual protection measures

Respiratory Protection

Not normally required. Use dust mask where dustiness is prevalent, or TLV is exceeded. In oxygen deficient atmospheres, use a self contained breathing apparatus, as an air purifying respirator will not provide protection.

Skin Protection

Gloves

Eye/Face Protection

Chemical goggles or safety glasses with side shields.



SAFETY DATA SHEET
Regular BCM Dry Chemical
(Fire Extinguishing Agent - Pressurized and Non-pressurized)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Body Protection
 Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Agent – Regular BCM Dry Chemical

Appearance

	Physical State	Solid (powder)
	Color	White
Odor		Odorless
Odor Threshold		No data available
pH		Not applicable
Specific Gravity		~2.3
Boiling Range/Point (°C/F)		Not applicable
Melting Point (°C/F)		No data available
Flash Point (PMCC) (°C/F)		Not flammable
Vapor Pressure		No data available
Evaporation Rate (BuAc=1)		No data available
Solubility in Water		16.4g/100g
Vapor Density (Air = 1)		Not applicable
VOC (g/l)		None
VOC (%)		None
Partition coefficient (n-octanol/water)		No data available
Viscosity		No data available
Auto-ignition Temperature		No data available
Decomposition Temperature		No data available
Upper explosive limit		No data available
Lower explosive limit		No data available
Flammability (solid, gas)		No data available

Expellant - Nitrogen

Appearance

	Physical State	Compressed gas
	Color	Colorless
Odor		None
Odor Threshold		No data available
pH		Not applicable
Specific Gravity		0.075 lb/ft ³ @70°F as vapor
Boiling Range/Point (°C/F)		-196°C/-321 °F
Melting Point (°C/F)		No data available
Flash Point (PMCC) (°C/F)		Not flammable
Vapor Pressure		838 psig @70°F and 1 atmosphere(Carbon Dioxide)
Evaporation Rate (BuAc=1)		No data available
Solubility in Water		No data available
Vapor Density (Air = 1)		Not applicable
VOC (g/l)		None
VOC (%)		None
Partition coefficient (n-octanol/water)		No data available
Viscosity		Not applicable



SAFETY DATA SHEET

Regular BCM Dry Chemical (Fire Extinguishing Agent - Pressurized and Non-pressurized)

9. PHYSICAL AND CHEMICAL PROPERTIES

Auto-ignition Temperature	No data available
Decomposition Temperature	No data available
Upper explosive limit	Not explosive
Lower explosive limit	Not explosive
Flammability (solid, gas)	Not flammable

10. STABILITY AND REACTIVITY

Reactivity

Pressurized containers may rupture or explode if exposed to heat.

Chemical Stability

Stable under normal conditions.

Possibility of hazardous reactions

Hazardous polymerization will not occur.

Conditions to Avoid

Exposure to direct sunlight - contact with incompatible materials

Incompatible Materials

Strong acids

Hazardous Decomposition Products

Oxides of carbon

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Sodium Bicarbonate:

Oral LD50 (Rat) >4000 mg/kg

Inhalation LC50(rat) >4.74 mg/l

Mica:

Oral LD50 (Rat) >2000 mg/kg

Nitrogen

Simple asphyxiant

Specific Target Organ Toxicity (STOT) – single exposure

Sodium Bicarbonate: Available data indicates this component is not expected to cause target organ effects after a single exposure

Nitrogen: Exposure to nitrogen gas at high concentrations can cause suffocation by reducing oxygen available for breathing. Breathing very high concentrations can cause dizziness, shortness of breath, unconsciousness or asphyxiation.

Specific Target Organ Toxicity (STOT) – repeat exposure

Sodium Bicarbonate: Available data indicates this component is not expected to cause target organ effects after repeat exposure.



SAFETY DATA SHEET

Regular BCM Dry Chemical (Fire Extinguishing Agent - Pressurized and Non-pressurized)

11. TOXICOLOGICAL INFORMATION

Serious Eye damage/Irritation

Sodium Bicarbonate: Slightly irritating (rabbit)

Mica: Not irritating (rabbit)

Skin Corrosion/Irritation

Sodium Bicarbonate: Slightly irritating (rabbit)

Mica: Not irritating (rabbit)

Respiratory or Skin Sensitization

No relevant studies identified.

Carcinogenicity

Mica may contain small quantities of quartz (crystalline silica) as an impurity. Prolonged exposure to respirable crystalline silica dust at concentrations exceeding the occupational exposure limits may increase the risk of developing a disabling lung disease known as silicosis. IARC has classified Silica Dust, Crystalline, in the form of quartz or cristobalite as 1 (carcinogenic to humans).

Germ Cell Mutagenicity

Sodium Bicarbonate: Negative test results in animal studies.

Reproductive Toxicity

Sodium Bicarbonate: Available data indicates this component is not expected to cause reproductive toxicity or birth defects.

Aspiration Hazard

Not an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Sodium Bicarbonate:

LC50 *Lepomis macrochirus* 7100 mg/l 96h

EC50 *Daphnia magna* 4100 mg/l 48h

Mobility in soil

No relevant studies identified.

Persistence/Degradability

No relevant studies identified.

Bioaccumulative Potential

No relevant studies identified.

Other adverse effects

No relevant studies identified.

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of container in accordance with all applicable local and national regulations.



SAFETY DATA SHEET

Regular BCM Dry Chemical (Fire Extinguishing Agent - Pressurized and Non-pressurized)

14. TRANSPORT INFORMATION

Safety Data Sheet information is intended to address a specific material and not various forms or states of containment.

Special Precautions for Shipping:

Individuals must be certified as Hazardous Material Shipper for all transportation modes. Pressurized Fire Extinguishers are considered a hazardous material by the US Department of Transportation and Transport Canada.

DOT CFR 172.101 Data	Fire extinguishers, 2.2, UN1044
UN Proper Shipping Name	Fire extinguishers
UN Class	(2.2)
UN Number	UN1044
UN Packaging Group	Not applicable
Classification for AIR Transportation (IATA)	Consult current IATA Regulations prior to shipping by air.
Classification for Water Transport IMDG	Consult current IMDG Regulations prior to shipping by water.

When shipping via ground, portable fire extinguishers pressurized to less than 241 psi and of less than 1100 cubic inches in size meet the requirements of "Limited Quantity" as referenced in 49 CFR 173.309 (2010). There is no limited quantity designation for fire extinguishers when shipped by air or water.

This section is believed to be accurate at the time of preparation. It is not intended to be a complete statement or summary of the applicable laws, rules, or hazardous material regulations, and is subject to change. Users have the responsibility to confirm compliance with all laws, rules, and hazardous material regulations in effect at the time of shipping.

15. REGULATORY INFORMATION

United States TSCA Inventory

This product contains ingredients that are listed on or exempt from listing on the EPA Toxic Substance Control Act Chemical Substance Inventory.

Canada DSL Inventory

All ingredients in this product are listed on the Domestic Substance List (DSL) or the Non-Domestic Substance List (NDSL) or are exempt from listing.

SARA Title III Sect. 311/312 Categorization: Pressurized

Pressure hazard

SARA Title III Sect. 311/312 Categorization: Non-pressurized

None

SARA Title III Sect. 313

This product does not contain any chemicals that are listed in Section 313 at or above de minimis concentrations.



SAFETY DATA SHEET

Regular BCM Dry Chemical (Fire Extinguishing Agent - Pressurized and Non-pressurized)

16. OTHER INFORMATION

NFPA Ratings

NFPA Code for Health - 1
NFPA Code for Flammability - 0
NFPA Code for Reactivity - 0
NFPA Code for Special Hazards - None

HMIS Ratings

HMIS Code for Health - 1
HMIS Code for Flammability - 0
HMIS Code for Physical Hazard - 0
HMIS Code for Personal Protection - See Section 8
*Chronic

Legend

ACGIH: American Conference of Governmental Industrial Hygienists
CAS#: Chemical Abstracts Service Number
EC50: Effect Concentration 50%
IARC: International Agency for Research on Cancer
LC50: Lethal Concentration 50%
LD50: Lethal Dose 50%
N/A: Denotes no applicable information found or available
OSHA: Occupational Safety and Health Administration
PEL: Permissible Exposure Limit
STEL: Short Term Exposure Limit
TLV: Threshold Limit Value
TSCA: Toxic Substance Control Act

Revision Date: November 23, 2016
Replaces: October 1, 2015
Changes made: Updated to company address.

Information Source and References

This SDS is prepared by Hazard Communication Specialists based on information provided by internal company references.

Prepared By: EnviroNet LLC.

The information and recommendations presented in this SDS are based on sources believed to be accurate. Badger Fire Protection assumes no liability for the accuracy or completeness of this information. It is the user's responsibility to determine the suitability of the material for their particular purposes. In particular, we make **NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED**, with respect to such information, and we assume no liability resulting from its use. Users should ensure that any use or disposal of the material is in accordance with applicable Federal, State, and local laws and regulations.